
Mobile generator sets HAC330GT**Set Model: HAC330GT**

Prime power/capacity (kw/kva):300/375	Stable voltage regulation: $\leq\pm 1\%$
Standby power/capacity (kw/kva): 330/412.5	Voltage fluctuation: $\leq\pm 0.5\%$
Power factor: : $\cos\Phi=0.8$	Transient voltage regulation: $+20\%\sim-15\%$
Rated output voltage (V): 400/230	Stable voltage time (s): ≤ 1
Rated current (prime/standby)(A): 541/595	Stable frequency regulation: $\leq\pm 1\%$
Rated speed (rpm):1500	Frequency fluctuation: $\leq\pm 0.5\%$
Rated frequency (Hz):50	Transient frequency regulation: $+10\%\sim-7\%$
Start:Auto/Recoil	Stable frequency time (s): ≤ 3
Fuel:0#	Oil consumption (100% loading)(g/kwh):209
N.W.(kg):5230	Noise(7m)(dB):70
Dimension(mm): 3350x1200x2650	

Diesel Engine

Brand: Cummins	Start: DC24V-electronic
producing area: Chongqing,China	Cooling: enclosed water cycle
Model: NTAA855-G7	Oil supply: DI
cylinder: 6	Speed regulation: electron
Borexstroke(mm): 140x152	Air suction: TCI
Compression ratio: 14.0:1	Overload capacity: 110%
Structure:in-line	Rotate speed(rpm): 1500

Alternator

Brand: Marathon	Insulation class: H
-----------------	---------------------



National HI-TECH Industrial & Development Zone, Zhengzhou, China
Tel: 0086-371-86525099

www.hamacpower.com

Producing area: Shanghai

Protection grade: IP21

Model: MP-300-4

Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 300/375

Voltage regulation:DVR

Rated voltage(v):400/230

Output frequency(Hz):50

Power factor: $\cos\Phi=0.8$

HAMAC