

## Open frame diesel generator HAC120G



Note: The photos of generator is only for your reference.

### Model: HAC120G

Prime power/capacity (kw/kva):110/137

Stable voltage regulation: $\leq\pm 1\%$

Standby power/capacity (kw/kva): 120/150

Voltage fluctuation:  $\leq\pm 0.5\%$

Power factor: :  $\cos\phi=0.8$

Transient voltage regulation: +20%~-15%

Rated output voltage (V): 400/230

Stable voltage time (s):  $\leq 1$

Rated current (prime/standby)(A): 198.4/216.5

Stable frequency regulation:  $\leq\pm 1\%$

Rated speed (rpm):1500

Frequency fluctuation:  $\leq\pm 0.5\%$

Rated frequency (Hz):50

Transient frequency regulation: +10%~-7%

Start: Auto/Recoil

Stable frequency time (s):  $\leq 3$

Fuel:0#

Oil consumption (100% loading)(g/kwh):208

N.W.(kg):1050

Noise(7m)(dB):85

Dimension(mm): 2300x790x1220

### Diesel Engine

Brand: Cummins

Start: DC24V-electronic

producing area: Xiangfan,China

Cooling: enclosed water cycle

Model: 6BTA5.9-G2

Oil supply: DI

cylinder: 6

Speed regulation: electron

Bore\*stroke(mm): 102x120

Air suction: TCI



National HI-TECH Industrial & Development Zone, Zhengzhou, China  
Tel: 0086-371-86525099

[www.hamacpower.com](http://www.hamacpower.com)

---

Compression ratio: 16.5:1                      Overload capacity: 110%

Structure:in-line                                      Rotate speed(rpm): 1500

**Alternator**

Brand: Marathon                                      Insulation class: H

Producing area: Shanghai                              Protection grade: IP21

Model: MP-104-4                                      Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 104/130                              Voltage regulation:DVR

Rated voltage(v):400/230                              Output frequency(Hz):50

Power factor:  $\text{COS}\Phi=0.8$

HAMAC