

Open frame diesel generator HAC550G



Note: The photos of generator are only for your reference.

Model: HAC550G

Prime power/capacity (kw/kva):500/625

Standby power/capacity (kw/kva): 550/687.5

Power factor: : $\cos\phi=0.8$

Rated output voltage (V): 400/230

Rated current (prime/standby)(A):902/992.2

Rated speed (rpm):1500

Rated frequency (Hz):50

Start:Auto/Recoil

Fuel:0#

N.W.(kg):5730

Dimension(mm): 3800x1810x2470

Diesel Engine

Brand: Cummins

producing area: Chongqing,China

Model: KT38-G

cylinder: 12

Borexstroke(mm): 159x159

Stable voltage regulation: $\leq\pm 1\%$

Voltage fluctuation: $\leq\pm 0.5\%$

Transient voltage regulation: +20%~-15%

Stable voltage time (s): ≤ 1

Stable frequency regulation: $\leq\pm 1\%$

Frequency fluctuation: $\leq\pm 0.5\%$

Transient frequency regulation: +10%~-7%

Stable frequency time (s): ≤ 3

Oil consumption (100% loading)(g/kwh):204

Noise(7m)(dB):92

Start: DC24V-electronic

Cooling: enclosed water cycle

Oil supply: DI

Speed regulation: electronic

Air suction: TCI



Compression ratio: 15.5:1

Overload capacity: 110%

Structure:v

Rotate speed(rpm): 1500

Alternator

Brand: Marathon

Insulation class: H

Producing area:Shanghai

Protection grade: IP21

Model: MP-500-4A/S

Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 500/625

Voltage regulation:DVR

Rated voltage(v):400/230

Output frequency(Hz):50

Power factor: $\text{COS}\Phi=0.8$

HAMAC