

Open frame diesel generator HAC880G





Note: The photos of generator are only for your reference.

Model: HAC880G

Prime power/capacity (kw/kva):800/1000

Standby power/capacity (kw/kva):880/1100

Power factor: : COSΦ=0.8

Rated output voltage (V): 400/230

Rated current (prime/standby)(A):1443/1587.5

Rated speed (rpm):1500

Rated frequency (Hz):50

Start:Auto/Recoil

Fuel:0#

N.W.(kg):6780

Dimension(mm): 4450x1810x2310

Diesel Engine

Brand: Cummins

producing area: Chongqing, China

Model: KTA38-G5

cylinder:12

Borexstroke(mm): 159x159

Stable voltage regulation:≤±1%

Voltage fluctuation: ≤±0.5%

Transient voltage regulation: +20%~-15%

Stable voltage time (s): ≤1

Stable frequency regulation: ≤±1%

Frequency fluctuation: ≤±0.5%

Transient frequency regulation: +10%~-7%

Stable frequency time (s): ≤3

Oil consumption (100% loading)(g/kwh):202

Noise(7m)(dB):95

Start: DC24V-electronic

Cooling: enclosed water cycle

Oil supply: DI

Speed regulation: electronic

Air suction:TCI



National HI-TECH Industrial & Development Zone, Zhengzhou, China Tel: 0086-371-86525099 www.hamacpower.com

Compression ratio: 13.9:1 Overload capacity: 110%

Structure:V Rotate speed(rpm): 1500

Alternator

Brand: Marathon Insulation class: H

Producing area:Shanghai Protection grade: IP21

Model: MX-850-4 Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 850/1062.5 Voltage regulation:DVR

Rated voltage(v):400/230 Output frequency(Hz):50

Power factor: COSΦ=0.8

